

PIPEHEAT-10 SELF-REGULATING HEATING CABLE WITH A PLUG

PipeHeat-10 is a self-regulating heating cable with a plug, of **10 W/m** output, and an Adflex (polyolefin) overjacket. **PipeHeat-10** can be installed directly on a pipe's surface or inserted into a pipe through a metal fitting otherwise.

PLUG and PLAY. PipeHeat-10 is designed for a direct connection: just plug it into a socket. When the temperature gets below 5°C, plug in the cable, or install a temperature control system, to save your time and money. The wide range of **PipeHeat-10** cables serves your choice for a proper length and power output that stops pipes from freezing.

Properties of heating cable:


- Self-regulating
- Special food-safe overjacket
- Small dimensions



 ϵ

TECHNICAL DATA





	40.44/	
Output	10 W/m	
Туре	Self-regulating	
Rated voltage	230V AC	
Cable dimensions	7.9x5.6 mm	
Connection cable	1.5m with plug	
Overjacket	Food-save (Adflex)	
Min. bending radius	35 mm	
Max. exposure temperature	+65°C	
Max. operating temperature	+65°C	
Min. installation temperature	-30°C	
Protection class	IP67	
Cable color	Violet	

PRODUCT LIST

TRODUCT LIST				
Type	Cable length (m)	Output (W)	Stock code	
PipeHeat-10 with a plug	1	10	33761001	
PipeHeat-10 with a plug	2	20	33761002	
PipeHeat-10 with a plug	3	30	33761003	
PipeHeat-10 with a plug	4	40	33761004	
PipeHeat-10 with a plug	5	50	33761005	
PipeHeat-10 with a plug	6	60	33761006	
PipeHeat-10 with a plug	7	70	33761007	
PipeHeat-10 with a plug	8	80	33761008	
PipeHeat-10 with a plug	9	90	33761009	
PipeHeat-10 with a plug	10	100	33761010	
PipeHeat-10 with a plug	11	110	33761011	
PipeHeat-10 with a plug	12	120	33761012	
PipeHeat-10 with a plug	15	150	33761015	
PipeHeat-10 with a plug	17	170	33761017	
PipeHeat-10 with a plug	20	200	33761020	
PipeHeat-10 with a plug	22	220	33761030	